

VOLVO 122 S



color combinations



A product of superb Swedish engineering

Light blue leatherette upholstery



Light grey



Light green



Light brown leatherette upholstery



Light grey leatherette upholstery

White



Slate blue



Black



Red with light grey top



AB VOLVO

**SALES
DEPARTMENT**

GÖTEBORG

SWEDEN

Importers:

VOLVO IMPORT, INC.,
462 Hudson Terrace,
Englewood Cliffs,
New Jersey

Distributors:

**VOLVO DISTRIBUTING,
INC.,**
452 Hudson Terrace
Englewood Cliffs,
New Jersey

**SWEDISH MOTOR
IMPORT, INC.,**
3301 West 12th Street,
Houston 24, Texas

AUTO IMPORTS, INC.,
5265 Riverside Drive,
Sherman Oaks, Calif.

(in Canada):

**AUTO IMPORTS
(SWEDISH) Ltd.**
Head Office
1130 W. Georgia St.
Vancouver 9, B. C.
Branch Office:
442 Conestoga Road,
Scarborough
(Toronto), Ont.

Engine
Four-cylinder, overhead valve, type B150

Bore
3.125"
Stroke
3.15"

Displacement
59 cu. in. (1.0 liter)
Compression ratio
8.2:1

Output
85 b.h.p. at 5,500 r.p.m.
Torque
37 lb.-ft. at 3,500 r.p.m.
Oil filler
Full-flow

Carburetors
Twin 30 horizontal
Transmission
Four-speed, fully synchronized

Rear axle
Hypoid type, Ratio 4.65:1
Steering gear
Dart and roller

Front suspension
Individual suspension with coil springs and con-

rod arms. Double-acting hydraulic telescopic shock absorbers. Stabilizer

Rear suspension
Coil springs. Rear axle carried on two tubular-mounted support arms, two torque arms and a track bar. Double-acting hydraulic, telescopic absorbers.

Foot brakes
Self-centering hydraulic Duo-Servo brakes, total brake lining area 165 sq. in.

Hand brake
Mechanical operation on rear wheels only.

Wheels
Pressed steel disc type. All wheels balanced
Tires
Tubeless, low pressure 3.95-15"

Body
All-weather, integral construction on steel body. Thoroughly rust-protected and completely undercoated.

Instrumentation
Padded instrument panel containing combined instrument with fuel gauge, temperature gauge, speedometer, odometer, tripmeter. Panel also contains warning lamps for battery charging, oil pressure, directional signals, headlamp beams.

Heater, defroster and fresh air system
Controls grouped in center of instrument panel.

Air intake in front of windshield
Safety belt fillings
Fittings for VOLVO safety belts.

Greasing
Greasing and oil change only necessary after every 3,000 miles

Wheelbase
100 1/2"

Overall length
135"

Overall width
65 1/2"

Height, unloaded
59 1/2"

Tread, front
51 1/2"

Tread, rear
61 1/2"

Weight
2,350 lb. (incl. fuel, oil, water)

The factory reserves the right to modify prices, design and equipment